



# RUST-X QUENCH 15

## High speed quenching with rust preventive additives

### Product Description

RUST-X Quenching oils are formulated using Group II base oils. These quenching oils perform better than the conventional oils due to

1. Better oxidation resistance contributing to the longer life of the oil
2. Higher flash point
3. Better film forming properties which impart even cooling to the component and hence provides even hardness and lower distortion or cracking
4. Higher quenching speed due to the special additives in the oil which provide faster cooling rates
5. Viscosity stability
6. Maintains the shine and surface finish of the components
7. Provides rust protection to the components

Application Method:  
Dipping

Property	Value
Kinematic Viscosity @ cSt @ 40°C	15 Cst
Specific Gravity	0.88 - 0.96
Flash Point	200d deg. C
Saponification Value (mg KOH/gm)	5.0-7.0
Sulphur Content	<0.5%
Ash Content	< 0.1%
Coverage (sq m/ Lt)	100-120
Effective Film thickness after drying	<1 micron
GM Magnetic Quenchometer	10 seconds

hi-tech international  
b-31 opp power house, chandigarh road, ludhiana  
b-100 ardee city, gurgaon, haryana  
No.17, dwarka raj park, pimplee saudagar, aundh, pune

w: [www.rustx.net](http://www.rustx.net) e: [info@rustx.net](mailto:info@rustx.net)  
delhi-maharashtra-chennai-ahmedabad-coimbatore-  
jamshedpur-punjab-haryana-j&k-hp-karnataka-mp

for longer life



T.A. C.KNOOP, AUSTRALIA