



RUST-X Refrox 32 , 46 and 68

RustX Refrox Refrigeration Oils are a high performance and low pour point lubricant designed exclusively for lubrication of refrigerating compressors. Refrox Oils have a highly refined petroleum oil with excellent oxidation stability, demulsification, and antirust properties. Because of its very low pour point, this oil is specially suitable for lubrication of compressors using R12, R22, R11, R113, R1381 and R502 as refrigerants, and also suitable for NH3 and Co2 refrigerant compressors.

Grade No.	32	46
Gravity, API, 15.6°C	28.7	26.8
Viscosity, Kin., cSt@40°C	30.17	46.04
@100°C	5.00	5.76
Viscosity Index	86	43
Flash Point, COC, °C	184	185
Pour Point, °C	-42	-36
TAN, mgKOH/g	0.01	0.01
Floc Point, °C	-50	-50
Color, D1500	L1.0	1.0
Product No.	Refrrox 32	Refrrox 46

hi-tech international
w79 midc taloja, mumbai
29, Gat 281/1 Kasaraboli, Pirangut, Pune
b-31 opp power house, chandigarh road, ludhiana
Ph: +91 161 3250700, 3260700 Fax: 2680791

w: www.rustx.net e:info@rustx.net
delhi-maharashtra-chennai-ahmedabad-coimbatore-
jamshedpur-punjab-haryana-j&k-hp-karnataka-mp

RUST-X
REST WITHOUT RUST

T.A. C.KNOOP, AUSTRALIA

for longer life